

# KUMHO PETROCHEMICAL

## Technical Data Sheet ( ISO )

### ABS(Acrylonitrile Butadiene Styrene)

### ABS 750SW

**Features** Super white, Easy flow, Medium impact strength

**Applications** Electronics, Household appliances, Miscellaneous goods

Physical	Test Method	Value
Specific gravity	ISO 1183	1.04
Melt Flow Index (220°C, 10kg)	ISO 1133	38g/10min
Water absorption	ISO 62	-%
Mold Shrinkage	ISO 294-4	0.5 0.8%

  

Mechanical	Test Method	Value
Tensile Strength(at yield)	ISO 527	46Mpa
Elongation(at break)	ISO 527	20%
Flexural Strength	ISO 178	73MPa
Flexural Modulus	ISO 178	2,500Mpa
Izod Impact Strength(23 °C )	ISO 180/1A	21KJ/m2
Charpy Impact Strength(23°C)	ISO 179/1eA	22KJ/m2
Rockwell Hardness(R scale)	ISO 2039-2	109

  

Thermal	Test Method	Value
Heat Deflection Temperature(1.8Mpa, Unannealed)	ISO 75-2	80°C
Heat Deflection Temperature(0.45Mpa, Unannealed)	ISO 75-2	91 °C
Vicat Softening Temperature(B50)	ISO 306	95°C

  

Flammability	Test Method	Value
Flame Rating - UL (1.6mm)	UL 94	HB